DOS HERMANAS

Vereda del Rayo, s/n Tel: +34 954 72 06 16 Fax: +34 954 72 11 30 41700 DOS HERMANAS (Sevilla) gpventas@gpacero.es 37° 17′ 54 N - 5° 54′ 43′′ O



G.P.

MANUFACTURAS DEL ACERO, S.A.

ALICANTE


C/Alisios, 35. Parcela 60 P.I. Plá de Vallonga Tel: +34 965 11 04 51 Fax: +34 91 681 68 52 31130 ALICANTE gpalicante@gpacero.es 38° 21′ 00 N - 0° 33′13′′ O



PINTO

C/Publicistas, 7 P.I. Ampliación Mateu Cromo Tel: +34 91 683 61 39 Fax: +34 91 681 68 52 28320 PINTO (Madrid) gpmadrid@gpacero.es 40° 14′ 59′′ N - 3° 43′ 30′′ O





WIRE IN BARS AND COILS

Bars and coils of quality B500T, B500S and B500SD according to Euronorm EN 10080.

Round plain and rib wire bars/coils, with the Adherence Certificate, for reinforced concrete.

Diameters from 6 to 25 mm

Standard length (bars): 6 and 12 mt.

Weight bars package/ coils: 1500/2500 Kgs

The mechanical properties of the steel are the followings:

	B5OOT	B5OOS	B5OOSD
Yield limit (fy)- N/mm2	≥500	≥500	≥500
Tensile Strength (fs)-N/mm2	≥550	≥550	≥575
Ratio (fs/fy)	≥1.03	≥1.05	1.15-1.35
Elongation to failure, (A5d) - %	8	12	16
Elongation at maximum load(Agt) - %	-	5.0	7.5



WELDED MESH

Our mesh is a CERTIFIED PRODUCT according to Euronorm EN-10080.

Quality B500T and B 500S (see above)

The welded mesh is made of rib wire or plain and the main use of it is for construction (reinforced concrete slabs, walls and fences).

The standard size of the mesh (length/width) for reinforced concrete is 600 * 220 cms and the usual grids are 15*15, 20*20, 15*30 and 20*30 cms. However, on request, we can produce other sizes and grids.

The current diameters used in mesh are 4,5,6,7,8,10 and 12 mm.

Weight package: 1500 / 3000 Kgs



LATTICE GIRDERS

Our Lattice girder is a CERTIFIED PRODUCT according to Euronorm EN-10080.

Quality B500T and B 500S.

The lattice girder is made of rib wire and the main use of it is for construction (reinforced concrete - floors).

The standard length is 6 and 13 mts. However, on request, we can produce other sizes

The current wire diameters used in the lattice girders are from 6 to 12 mm.

Weight package: 500 / 1500 Kgs



TUBES

Grade DD11 S235JR S275JOH

Length	4/12 m
Thickness	1.5/6 mm
Round	12/127 mm
Square	12×12 / 100×100
Rectangular	20×10 / 120×80
Packages	900-1500 kg



ROLLED SHEET

Hot rolled sheet

Grade	S235JR/S275JOH
Thickness	1.5 – 8 mm
Length	1 – 12 m
Width	1 - 1.25 - 1.5 m
Packages	1000 - 3000 kg

Galvanised roofing sheet

Thickness	Q5-1mm
Roofing	sinusoidal and trapezoidal profile
Length	2.5 – 12 m

Cold and galvanised sheet

Thickness	O.5-3 mm
Roofing	O.2-4 m
Length	1–2 m



QUALITY CONTROL

All our products are produced under the strictest quality control.

The company is certified under the International Standard ISO 9001.

Bars, Welded Mesh and Lattice Girders are certified products according to Euronorm EN 10080.

Tubes and planes have the CE marking, according to Euronorm EN 10219

